

**M12 male 0° A-cod. with cable shielded**

PUR 12x0.14 shielded bk UL/CSA+drag ch. 10m

Male straight

M12, 12-pole



shielded

with cable sleeves


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta



Cable length

10 m

**Side 1**

Tightening torque

0,6 Nm

Tämän tietolomakkeen tiedot on laadittu suurimmalla mahdollisella huolellisuudella.

Vahingonkorvausvastuu koskien tietojen oikeellisuutta, laajuutta ja ajankohtaisuutta kattaa ainoastaan törkeän laiminlyönnin. Versio: 02.06.2024

Murrelektronik Power Oy | Jussilankatu 6 | 15680 Lahti | Fon +358 20 7789810 | Fax +358 20 7789811 | shop@murrelektronik.fi | shop.murrelektronik.fi

|                                     |                   |
|-------------------------------------|-------------------|
| Mounting method                     | inserted, screwed |
| Family construction form            | M12               |
| Thread                              | M12 x 1           |
| Coding                              | A                 |
| Material                            | PUR               |
| Width across flats                  | SW13              |
| Degree of protection (EN IEC 60529) | IP65, IP66K, IP67 |

#### Kaupalliset tiedot

|             |               |
|-------------|---------------|
| ECLASS-6.0  | 27279218      |
| ECLASS-6.1  | 27279218      |
| ECLASS-7.0  | 27279218      |
| ECLASS-8.0  | 27279218      |
| ECLASS-9.0  | 27060311      |
| ECLASS-10.1 | 27060311      |
| ECLASS-11.1 | 27060311      |
| ECLASS-12.0 | 27060311      |
| ETIM-5.0    | EC001855      |
| GTIN        | 4048879188838 |
| Pakkauskoko | 1             |
| Tullinumero | 85444290      |

#### Electrical data | Supply

|                                    |       |
|------------------------------------|-------|
| Operating voltage AC max.          | 30 V  |
| Operating voltage DC max.          | 30 V  |
| Operating voltage AC (UL-listed)   | 30 V  |
| Operating voltage DC (UL-listed)   | 30 V  |
| Current operating per contact max. | 1,5 A |

#### Installation | Connection

|              |         |
|--------------|---------|
| Mounting set | M12 x 1 |
|--------------|---------|

#### Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 0,8 kV            |
| Material group (IEC 60664-1)           | I                 |

#### Mechanical data | Material data

|                           |                  |
|---------------------------|------------------|
| Coating locking           | Nickeled         |
| Coating of fitting        | nickel plated    |
| Locking material          | Zinc die-casting |
| Material screw connection | Zinc die-casting |

#### Mechanical data | Mounting data

|                 |                                       |
|-----------------|---------------------------------------|
| Mounting method | inserted, screwed, Shaking protection |
|-----------------|---------------------------------------|

#### Environmental characteristics | Climatic

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating temperature min.             | -25 °C                     |
| Operating temperature max.             | 85 °C                      |
| Additional condition temperature range | depending on cable quality |

#### Important installation notes

|                        |                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note on strain relief  | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |

#### Conformity

|                  |                          |
|------------------|--------------------------|
| Product standard | DIN EN 61076-2-101 (M12) |
|------------------|--------------------------|

#### Installation | Cable

|                                                   |                                                                                        |
|---------------------------------------------------|----------------------------------------------------------------------------------------|
| wire arrangement                                  | gray-pink, violet, red-blue, brown, red, gray, black, yellow, pink, green, white, blue |
| Cable identification                              | 706                                                                                    |
| Cable Type                                        | 3                                                                                      |
| Jacket Color                                      | black                                                                                  |
| Type of Certificate                               | cURus                                                                                  |
| Amount stranding                                  | 1                                                                                      |
| Stranding                                         | 3 wires twisted                                                                        |
| Amount stranding (type 2)                         | 1                                                                                      |
| Stranding (type 2)                                | 9 wires around Stranding combination twisted                                           |
| Cable shielding (type)                            | copper braid, tinned                                                                   |
| Cable shielding (coverage)                        | 80 %                                                                                   |
| Banding                                           | Fleece, Foil                                                                           |
| wire arrangement                                  | gray-pink, violet, red-blue, brown, red, gray, black, yellow, pink, green, white, blue |
| Cable weight                                      | 67,1 g/m                                                                               |
| Material jacket                                   | PUR                                                                                    |
| Shore hardness jacket                             | 90 ± 5 Shore A                                                                         |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Outer-diameter (jacket)                           | 6,5 mm                                                                                 |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                                                  |
| Material wire insulation                          | PP                                                                                     |
| Amount wires                                      | 12                                                                                     |
| Outer diameter insulation                         | 1 mm                                                                                   |
| Outer diameter tolerance core insulation          | ± 5 %                                                                                  |
| Shore hardness wire insulation                    | 70 ± 5 Shore D                                                                         |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Amount strands (wire)                             | 18                                                                                     |
| Diameter of single wires                          | 0,1 mm                                                                                 |
| Conductor crosssection (wire)                     | 0,14 mm²                                                                               |
| Material conductor wire                           | Stranded copper wire, bare                                                             |
| Conductor type (wire)                             | strand class 6                                                                         |
| Nominal voltage AC max.                           | 300 V                                                                                  |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                                                      |
| Current load capacity min. wire                   | 2 A                                                                                    |
| Electrical resistance line constant wire          | 138 Ω/km @ 20 °C                                                                       |
| AC withstand voltage (wire - wire)                | 2 kV @ 60 s                                                                            |
| Power frequency withstand voltage (wire - jacket) | 2 kV @ 60 s                                                                            |
| AC withstand voltage (wire - shield)              | 2 kV @ 60 s                                                                            |
| Min. operating temperature (static)               | -40 °C                                                                                 |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                                                      |
| Operating temperature min. (dynamic)              | -25 °C                                                                                 |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                                                      |
| UV resistance                                     | DIN EN ISO 4892-2 A                                                                    |
| Flame resistance                                  | UL 1581 § 1100 FT2   IEC 60332-2-2   UL 1581 § 1090                                    |
| chemical resistance                               | Good, application-related testing                                                      |
| Gasoline resistance                               | Good, application-related testing                                                      |
| Oil resistance                                    | Good, application-related testing   DIN EN 60811-404                                   |
| Bending radius (fixed)                            | 5 x Outer diameter                                                                     |
| Bending radius (dynamic)                          | 10 x Outer diameter                                                                    |
| No. of bending cycles (C-track)                   | 5 Mio. @ 25 °C                                                                         |
| Traversing distance (C-track)                     | 5 m @ 25 °C   horizontal                                                               |
| Travel speed (C-track)                            | 3,3 m/s @ 25 °C                                                                        |
| No. of torsion cycles                             | 2 Mio.                                                                                 |
| Torsion stress                                    | ± 30 °/m                                                                               |

Torsion speed

35 cycles/min