

CAN-PLUG-MALE (SUB-D) 90°

Screw terminals up to 1Mbits/s

Bus connection plug 90°

SUB-D9 (female), screw terminals

max. 1 Mbit/s with switchable terminal resistors

CANopen

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta

Kaupalliset tiedot

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ECLASS-10.1	27242692
ECLASS-11.1	27242692
ECLASS-12.0	27242692
ETIM-5.0	EC002584
GTIN	4048879049825
Pakkauskoko	1
Tullinumero	85366990

Electrical data

Terminating resistor	connectable, integrated
----------------------	-------------------------

Industrial communication

Data transmission rate max.	1 MBit/s
-----------------------------	----------

Installation

Connection cross section max.	1 mm ²
-------------------------------	-------------------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP20
-------------------------------------	------

Mechanical data | Mounting data

Height	65 mm
--------	-------

Width	48 mm
Depth	16 mm
Environmental characteristics Climatic	
Operating temperature min.	0 °C
Operating temperature max.	60 °C
Storage temperature min.	-25 °C
Storage temperature max.	80 °C
Connection type 2	
Family construction form	D-Sub
Gender	female
No. of poles	9
PIN 2	CAN_L
PIN 3	CAN_GND
PIN 5	CAN_SHLD
PIN 6	0 V
PIN 7	CAN_H
PIN 9	CAN V +
Connection	Screw terminals SK
Family construction form	terminal
Gender	female
No. of poles	6