

SUPPRESSOR FOR CONTACTORS

VDR, 48 VAC/DC, 70 VA/W

48 V AC/DC

VDR

For other configurations and voltages, please inquire.

Link to Product

Illustration



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27371013 |
| ECLASS-6.1      | 27371013 |
| ECLASS-7.0      | 27371013 |
| ECLASS-8.0      | 27371013 |
| ECLASS-9.0      | 27371013 |
| ECLASS-10.1     | 27371013 |

|                       |               |
|-----------------------|---------------|
| ECLASS-11.1           | 27371013      |
| ECLASS-12.0           | 27371013      |
| ETIM-5.0              | EC002498      |
| customs tariff number | 85363010      |
| GTIN                  | 4048879018159 |
| Packaging unit        | 1             |

#### Compatibility | Compatible with

|                        |           |
|------------------------|-----------|
| Appropriate contactors | universal |
|------------------------|-----------|

#### Electrical data

|                    |         |
|--------------------|---------|
| Damping factor     | 1.5× UN |
| Holding power max. | 70 W    |

#### Electrical data | Input

|                       |      |
|-----------------------|------|
| Input voltage AC min. | 24 V |
| Input voltage AC max. | 48 V |
| Input voltage DC min. | 24 V |
| Input voltage DC max. | 48 V |

#### Installation | Connection

|                        |                           |
|------------------------|---------------------------|
| Connection information | self-securing cable forks |
|------------------------|---------------------------|

#### Device protection | Media

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

#### Mechanical data | Material data

|                                     |         |
|-------------------------------------|---------|
| Combustibility class housing (UL94) | V-0     |
| Material housing                    | Plastic |

#### Mechanical data | Mounting data

|        |       |
|--------|-------|
| Height | 30 mm |
| Width  | 20 mm |
| Depth  | 13 mm |

#### Environmental characteristics | Climatic

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C  |