

MPOT POTENTIOMETER MODULE

1K-Ohm/3600° /10 turn

10-turn potentiometer

1 kΩ


The 10-turn potentiometer has a decimal scale and locking lever

The potentiometer modules are fitted with standard values. They are available as 270° potentiometer and as 10-turn potentiometer with fine adjustment. They can be operated with 10 V DC or 24 V DC. A resistor reduces the voltage so that a 24 V DC voltage can be reduced to operate between approx. 0...11 V. The connection is via terminals.

Link to Product

Illustration





Product may differ from Image

Commercial data		
ECLASS-6.0	27371227	
ECLASS-6.1	27371227	
ECLASS-7.0	27371227	
ECLASS-8.0	27371227	
ECLASS-9.0	27371227	
ECLASS-10.1	27371227	
ECLASS-11.1	27371227	
ECLASS-12.0	27371227	
ETIM-5.0	EC001027	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-25

Murrelektronik Power Oy | Jussilankatu 6 | 15680 Lahti | Fon +358 20 7789810 | Fax +358 20 7789811 | shop@murrelektronik.fi | shop.murrelektronik.fi



customs tariff number	85334010
GTIN	4048879041652
Packaging unit	1
Electrical data	
Power max.	1,4 W
Linearity	±0,25 %
Resistance	1 κΩ
Resistance tolerance	5 %
Electrical data Input	
Power loss max.	0,25 W
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	75 mm
Width	45 mm
Depth	65 mm
Environmental characteristics Climatic	
Operating temperature min.	O° 0
Operating temperature max.	60 °C

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-25

Murrelektronik Power Oy | Jussilankatu 6 | 15680 Lahti | Fon +358 20 7789810 | Fax +358 20 7789811 | shop@murrelektronik.fi | shop.murrelektronik.fi