

LED - LT 24/GREEN

(green)  
24 V DC  
with lamp test input  
The modules are suitable for wall thickness of 1.5...5.0 mm.

Link to Product

Illustration



Product may differ from Image

| Commercial data                     |                   |
|-------------------------------------|-------------------|
| ECLASS-6.0                          | 27261590          |
| ECLASS-6.1                          | 27261501          |
| ECLASS-7.0                          | 27261501          |
| ECLASS-8.0                          | 27261501          |
| ECLASS-9.0                          | 27261501          |
| ECLASS-10.1                         | 27261501          |
| ECLASS-11.1                         | 27261501          |
| ECLASS-12.0                         | 27261501          |
| ETIM-5.0                            | EC000272          |
| customs tariff number               | 85318070          |
| GTIN                                | 4048879041225     |
| Packaging unit                      | 10                |
| Electrical data   Supply            |                   |
| Operating voltage DC                | 24 V              |
| Operating voltage DC min.           | 20,4 V            |
| Operating voltage DC max.           | 26,4 V            |
| Current consumption max.            | 10 mA             |
| Installation   Connection           |                   |
| Connection information              | Faston 2.8×0.8 mm |
| Device protection   Electrical      |                   |
| Degree of protection (EN IEC 60529) | IP65              |
| Device protection   Media           |                   |
| Flame resistance                    | flame retardant   |
| Mechanical data                     |                   |
| Diameter LED                        | 5 mm              |

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Material housing | Plastic |
|------------------|---------|

**Mechanical data | Mounting data**

|                               |      |
|-------------------------------|------|
| Diameter front panel drilling | 9 mm |
|-------------------------------|------|

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
|----------------------------|--------|

|                            |       |
|----------------------------|-------|
| Operating temperature max. | 50 °C |
|----------------------------|-------|