MURR ELEKTRONIK
stay connected

## LED-display yellow 24VDC IP67 lamptest


Product discontinued, no alternative


(yellow)
24 V DC
Protection IP67
with lamp test input

[Link to Product]

### Illustration




Product may differ from Image

| Commercial data | |
|---|---|
| ECLASS-6.0 | 27261590 |
| ECLASS-7.0 | 27261590 |
| ECLASS-8.0 | 27261590 |
| ECLASS-9.0 | 27261590 |
| ETIM-5.0 | EC000272 |
| customs tariff number | 85318070 |
| GTIN | 4048879040600 |
| Packaging unit | 10 |

| Electrical data \| Supply | |
|---|---|
| Operating voltage AC | 24 V |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

| | |
|---|---|
| Operating voltage AC min. | 20,4 V |
| Operating voltage AC max. | 26,4 V |
| Operating voltage DC | 24 V |
| Operating voltage DC min. | 20,4 V |
| Operating voltage DC max. | 26,4 V |
| Current consumption min. | 13 mA |
| Current consumption max. | 17 mA |
| **Installation \| Connection** | |
| Connection information | Faston 2.8×0.8 mm |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP67 |
| **Mechanical data** | |
| Diameter LED | 5 mm |
| **Mechanical data \| Material data** | |
| Color housing | gray |
| Material housing | PVC |
| **Mechanical data \| Mounting data** | |
| Diameter front panel drilling | 8 mm |
| Height | 18,5 mm |
| Width | 12 mm |
| Depth | 53 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -40 °C |
| Operating temperature max. | 70 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29