MURR ELEKTRONIK
stay connected

**MCS POWER SUPPLY 3-PHASE,**


IN: 360-550VAC OUT: 24-28V/10ADC


INPUT: 3× 360...550 V AC
OUTPUT: 24...28 V DC
Current: 10 A

## Link to Product

### Illustration






Product may differ from Image

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27049002 |
| ECLASS-6.1 | 27049002 |
| ECLASS-7.0 | 27049002 |
| ECLASS-8.0 | 27049002 |
| ECLASS-9.0 | 27040701 |
| ECLASS-10.1 | 27040701 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27040701 |
| ECLASS-12.0 | 27040701 |
| ETIM-5.0 | EC002540 |
| customs tariff number | 85044083 |
| GTIN | 4048879080583 |
| Packaging unit | 1 |
| **Electrical data** | |
| Number of devices parallel connection max. | 5 |
| Number of devices series connection max. | 2 |
| Parallel connection | yes |
| Series connection | yes |
| Security level | SELV |
| **Electrical data \| Supply** | |
| Power frequency | 50 ... 60 Hz |
| **Electrical data \| Input** | |
| Input voltage AC min. | 360 V |
| Input voltage AC max. | 550 V |
| Input current AC (3-phase) | 0,65 A |
| Inrush current max. | 15 A |
| External back-up fuse per phase max. | 2 A |
| Phase number input | 3 |
| Efficiency | 90 % |
| **Electrical data \| Output** | |
| Selectable switch-off mode | front sided plug link (automatic re-start or definite shut-off) |
| Output voltage DC | 24 V |
| Output voltage DC min. | 24 V |
| Output voltage DC max. | 28 V |
| Output voltage adjustable | yes |
| Output current | 10 A |
| Output current (UL) | 12 A |
| Mains failure bridging min. | 11 ms @ 400 V AC |
| Ripple effective max. | 20 mV |
| Spikes (s-s) max. | 100 mV |
| **Device protection \| Electrical** | |
| Short-circuit protection output | yes |
| Overload protection output | yes |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height | 127 mm |
| Width | 68 mm |
| Depth | 198 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | 0 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -25 °C |
| Storage temperature max. | 85 °C |
| Relative humidity min. (operation) | 5 % |
| Relative humidity max. (operation) | 95 % no condensation |
| **Connection type 2** | |
| Connection | Spring clamp terminals FK |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 4 |
| PIN 1 | PE |
| PIN 2 | L 1 |
| PIN 3 | L 2 |
| PIN 4 | L 3 |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | green |
| No. of poles | 4 |
| PIN 1 | - |
| PIN 2 | - |
| PIN 3 | + |
| PIN 4 | + |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-29