


**MIRO 6.2 OPTO-COUPLER MODULE**

IN: 30 VDC - OUT: 48 VDC / 1 A

Transistor 1 A  
24 V DC  
Spring clamp terminals

[Link to Product](#)

**Illustration**



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27371601 |
| ECLASS-6.1      | 27371604 |
| ECLASS-7.0      | 27371604 |
| ECLASS-8.0      | 27371604 |
| ECLASS-9.0      | 27371604 |
| ECLASS-10.1     | 27371604 |

|                       |               |
|-----------------------|---------------|
| ECLASS-11.1           | 27371604      |
| ECLASS-12.0           | 27371604      |
| ETIM-5.0              | EC001504      |
| customs tariff number | 85414900      |
| GTIN                  | 4048879021760 |
| Packaging unit        | 1             |

**Electrical data | Input**

|                           |         |
|---------------------------|---------|
| Input voltage OFF DC min. | 0 V     |
| Input voltage OFF DC max. | 5 V     |
| Input voltage DC min.     | 11 V    |
| Input voltage DC max.     | 30 V    |
| Current input DC          | 6,25 mA |

**Electrical data | Output**

|                                      |          |
|--------------------------------------|----------|
| Switch-off delay resistive load max. | 1000 µs  |
| On-delay resistive load max.         | 1500 µs  |
| Quiescent current OFF max.           | 0,025 mA |
| Switching frequency inductive max.   | 4 Hz     |
| Switching frequency ohmic max.       | 40 Hz    |
| Voltage switching DC min.            | 3 V      |
| Switching voltage DC max.            | 48 V     |
| Switching current min.               | 0,5 mA   |
| Switching current max.               | 1 A      |
| Voltage drop DC max.                 | 0,12 V   |

**Diagnostics**

|                       |        |
|-----------------------|--------|
| Status indication LED | yellow |
|-----------------------|--------|

**Device protection | Electrical**

|                          |       |
|--------------------------|-------|
| Rated insulation voltage | 500 V |
|--------------------------|-------|

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Color housing    | black   |
| Material housing | Plastic |

**Mechanical data | Mounting data**

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 78 mm                     |
| Width                      | 6,2 mm                    |
| Depth                      | 70 mm                     |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |

**Connection type 4**

|                          |                           |
|--------------------------|---------------------------|
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | 14                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |

|                          |                           |
|--------------------------|---------------------------|
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | 13                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | + A 1                     |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | - A 2                     |