

MODLINK MSDD SINGLE COMBI INSERT ITALY

1x SUB-D9 ST/BU

- 1x Italy (CEI 23-16)
- 1x SUB-D9 (male/female)
- 1x SUB-D9 cut-out

Link to Product

Illustration



Product may differ from Image



Commercial data	
ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-8.0	27189217
ECLASS-9.0	27182806
ECLASS-10.1	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806
ETIM-5.0	EC000020
customs tariff number	85366990
GTIN	4048879601054
Packaging unit	1
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP20
Mechanical data Mounting data	
Height	87,5 mm
Width	50,7 mm
Depth	30,7 mm
Environmental characteristics Climatic	
Operating temperature min.	-5 °C
Operating temperature max.	50 °C

Storage temperature min.	-10 °C
--------------------------	--------

Storage temperature max.	60 °C
--------------------------	-------

Shielding plate

Connection information	Threaded hole M4
------------------------	------------------

Tightening torque	0,9 Nm
-------------------	--------

Italy (CEI 23-16)

Connection cross section max.	4 mm ²
-------------------------------	-------------------

AWG number max.	12
-----------------	----

Operating voltage AC	250 V
----------------------	-------

Operating current	16 A
-------------------	------

Connection	Screw terminals SK
------------	--------------------

No. of poles	2 + PE
--------------	--------

Connections per pole	2
----------------------	---

SUB-D9

Operating voltage AC	48 V
----------------------	------

Operating voltage DC	48 V
----------------------	------

Operating voltage AC max. (UL-listed)	30 V
---------------------------------------	------

Operating voltage DC max. (UL-listed)	42,4 V
---------------------------------------	--------

Operating current	3 A
-------------------	-----

Current operating max. (UL)	175 mA
-----------------------------	--------

Family construction form	SUB-D9
--------------------------	--------

Family type Back side	SUB-D9
-----------------------	--------

Gender	male
--------	------

Gender Rear	female
-------------	--------

Looking techniques	Standard UNC 4-40 screw thread bolt (EN 60807)
--------------------	--

No. of poles	9
--------------	---