

COMLIGHT57 LED RED STATUS LIGHT

Product discontinued

Compact status light  
red  
clear

Link to Product

Illustration



Product may differ from Image

| Commercial data                          |                  |
|------------------------------------------|------------------|
| ECLASS-6.0                               | 27371220         |
| ECLASS-7.0                               | 27371220         |
| ECLASS-8.0                               | 27371220         |
| ECLASS-9.0                               | 27371220         |
| ETIM-5.0                                 | EC000232         |
| customs tariff number                    | 85318070         |
| GTIN                                     | 4048879448659    |
| Packaging unit                           | 1                |
| Electrical data   Supply                 |                  |
| Operating voltage DC                     | 24 V             |
| Current consumption max.                 | 25,9 mA          |
| Device protection   Electrical           |                  |
| Degree of protection (EN IEC 60529)      | IP65             |
| Additional condition protection degree   | inserted, locked |
| Mechanical data   Material data          |                  |
| Material housing                         | Plastic          |
| Mechanical data   Mounting data          |                  |
| Height                                   | 61 mm            |
| Width                                    | 57 mm            |
| Depth                                    | 57 mm            |
| Environmental characteristics   Climatic |                  |
| Operating temperature min.               | -30 °C           |
| Operating temperature max.               | 50 °C            |
| Connection type 1                        |                  |

|                          |            |
|--------------------------|------------|
| Family construction form | M12        |
| Gender                   | male       |
| Coding                   | A          |
| No. of poles             | 4          |
| PIN 3                    | BU 0 V     |
| PIN 4                    | BK 24 V DC |