

**Modlight50 Pro LED modul clear**

Input 24VDC

LED module (clear)

[Link to Product](#)**Illustration**

Product may differ from Image

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27371200      |
| ECLASS-6.1            | 27371220      |
| ECLASS-7.0            | 27371220      |
| ECLASS-8.0            | 27371220      |
| ECLASS-9.0            | 27371220      |
| ECLASS-10.1           | 27371220      |
| ECLASS-11.1           | 27371220      |
| ECLASS-12.0           | 27371220      |
| ETIM-5.0              | EC000232      |
| customs tariff number | 85319000      |
| GTIN                  | 4048879751544 |
| Packaging unit        | 1             |

**Electrical data | Supply**

|                           |         |
|---------------------------|---------|
| Operating voltage DC      | 24 V    |
| Operating voltage DC min. | 21,6 V  |
| Operating voltage DC max. | 26,4 V  |
| Current consumption max.  | 62,5 mA |

**Device protection | Electrical**

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

**Mechanical data | Material data**

|                  |    |
|------------------|----|
| Material housing | PC |
|------------------|----|

**Mechanical data | Mounting data**

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-06

Murrelektronik Power Oy | Jussilankatu 6 | 15680 Lahti | Fon +358 20 7789810 | Fax +358 20 7789811 | shop@murrelektronik.fi | shop.murrelektronik.fi

|        |       |
|--------|-------|
| Height | 52 mm |
| Width  | 50 mm |
| Depth  | 50 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 60 °C  |

**Connection type 1**

|                 |                 |
|-----------------|-----------------|
| Mounting method | bayonet-locking |
|-----------------|-----------------|