

**Modlight70 Pro LED modul clear**

Input 24VDC

LED module (clear)

[Link to Product](#)

Illustration



Product may differ from Image



Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27371200      |
| ECLASS-6.1            | 27371220      |
| ECLASS-7.0            | 27371220      |
| ECLASS-8.0            | 27371220      |
| ECLASS-9.0            | 27371220      |
| ECLASS-10.1           | 27371220      |
| ECLASS-11.1           | 27371220      |
| ECLASS-12.0           | 27371220      |
| ETIM-5.0              | EC000232      |
| customs tariff number | 85319000      |
| GTIN                  | 4048879752466 |
| Packaging unit        | 1             |

Electrical data | Supply

|                           |         |
|---------------------------|---------|
| Operating voltage DC      | 24 V    |
| Operating voltage DC min. | 21,6 V  |
| Operating voltage DC max. | 26,4 V  |
| Current consumption max.  | 62,5 mA |

Device protection | Electrical

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

Mechanical data | Material data

|                  |    |
|------------------|----|
| Material housing | PC |
|------------------|----|

Mechanical data | Mounting data

|                                                 |                 |
|-------------------------------------------------|-----------------|
| Height                                          | 49 mm           |
| Width                                           | 70 mm           |
| Depth                                           | 70 mm           |
| <b>Environmental characteristics   Climatic</b> |                 |
| Operating temperature min.                      | -30 °C          |
| Operating temperature max.                      | 60 °C           |
| <b>Connection type 1</b>                        |                 |
| Mounting method                                 | bayonet-locking |