



M12 female 0° A-cod. screw terminal V4A

5-pol., max. 0,75mm², 6 - 8mm


Female straight  
M12, 5-pole  
Sealing range (cable Ø): 6...8 mm  
Stainless steel 1.4404 (V4A)  
Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration



Product may differ from Image



Side 1

|                                     |      |
|-------------------------------------|------|
| Family construction form            | M12  |
| Degree of protection (EN IEC 60529) | IP67 |

Commercial data

|            |          |
|------------|----------|
| ECLASS-6.0 | 27279221 |
|------------|----------|

|                       |               |
|-----------------------|---------------|
| ECLASS-7.0            | 27440104      |
| ECLASS-8.0            | 27440104      |
| ECLASS-9.0            | 27440102      |
| ECLASS-10.1           | 27440102      |
| ECLASS-11.1           | 27440102      |
| ECLASS-12.0           | 27440116      |
| ETIM-5.0              | EC002635      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879110938 |
| Packaging unit        | 1             |

#### Electrical data | Supply

|                                           |      |
|-------------------------------------------|------|
| Operating voltage DC max.                 | 60 V |
| Current operating per contact max.        | 4 A  |
| Current operating per contact max. (URc.) | 3 A  |

#### Installation

|                               |                      |
|-------------------------------|----------------------|
| Connection cross section max. | 0,75 mm <sup>2</sup> |
|-------------------------------|----------------------|

#### Installation | Connection

|                    |         |
|--------------------|---------|
| Tightening torque  | 0,6 Nm  |
| Mounting set       | M12 x 1 |
| Width across flats | SW18    |

#### Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 0,8 kV            |
| Overvoltage category (EN 60664-1)      | III               |
| Overvoltage category (EN 60950-1)      | II                |

#### Mechanical data | Material data

|                  |                              |
|------------------|------------------------------|
| Material housing | PA                           |
| Locking material | Stainless steel 1.4404 (V4A) |

#### Mechanical data | Mounting data

|                     |                                       |
|---------------------|---------------------------------------|
| Mounting method     | inserted, screwed, Shaking protection |
| Clamping range min. | 6 mm                                  |
| Clamping range max. | 8 mm                                  |
| Height              | 54 mm                                 |
| Width               | 20 mm                                 |
| Depth               | 20 mm                                 |

#### Environmental characteristics | Climatic

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -40 °C |
| Operating temperature max. | 85 °C  |

#### Important installation notes

|                        |                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note on strain relief  | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |