

Single locking lever, top entry M20

B6
Hood (low)
Single locking lever
Cable outlet straight (M20)
IP65
Technical data will be only guaranteed with Murrelektronik components.

Illustration



Technical drawing of the M20x1.5-8H nut, showing two views: a front view (left) and a side view (right). The front view shows a hexagonal nut with a central hole, with a width dimension of 43. The side view shows the nut's profile, with a height dimension of 51 and a base width dimension of 60. The thread specification M20x1.5-8H is indicated on the side view.

ECLASS-6.0	27143424
ECLASS-6.1	27261203
ECLASS-7.0	27440202
ECLASS-8.0	27440202
ECLASS-9.0	27440202
ECLASS-10.1	27440202
ECLASS-11.1	27440202
ECLASS-12.0	27440202
ETIM-5.0	EC000437
customs tariff number	85389099
GTIN	4048879644075
Packaging unit	1

Cable outlet	straight
--------------	----------

Mounting set	M20
Mating cycles min.	500

Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked, with screw connection

Housing type	Hood
Public housing	100%
Private housing	100%
Homeless	100%
Other	100%

Mechanical data Material data	
Coating housing	powder-coated
Coating locking	verzinkt
Material housing	Aluminum die casting
Locking material	Steel
Mechanical data Mounting data	
Size	B6
Height	51 mm
Width	43 mm
Depth	60 mm
Locking techniques	Single locking lever
Environmental characteristics Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	100 °C
Climatic category (EN IEC 60068-1)	40/100/21