




PKB 2 FOR SIGNAL TRANSFER

250V / 25 A

4× 22-pole

25 A per potential rail

Screw plug-in terminals

Input terminal: max. 6 mm² single core, total current: max. 100 A
[Linkki tuotteeseen](#)
Kuvat


Tuote voi erota kuvassa olevasta


Kaupalliset tiedot

ECLASS-6.0	27143424
ECLASS-6.1	27260708
ECLASS-7.0	27141152
ECLASS-8.0	27141152
ECLASS-9.0	27141152
ECLASS-10.1	27141152

ECLASS-11.1	27141152
ECLASS-12.0	27141152
ETIM-5.0	EC001283
GTIN	4048879026055
Pakkauskoko	1
Tullinumero	85369010
Electrical data Supply	
Operating voltage AC	250 V
Total current per potential rail max.	25 A
Installation	
Connection cross-section solid max.	6 mm ²
Connection cross-section stranded/fine-stranded max.	4 mm ²
AWG number	9
Installation Connection	
Connection	Screw terminals SK
Device protection Electrical	
Overvoltage category (EN 60664-1)	II
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	75 mm
Width	135 mm
Depth	66 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C