

CUBE67 ACCESSORIES

System interface connector

M12

Female straight

Internal system connection
with mounting socket


Flange, hole spacing 30 mm, bore 3.3 mm

[Linkki tuotteeseen](#)

Kuvat



Tuote voi erota kuvassa olevasta



Kaupalliset tiedot

ECLASS-6.0	27242692
ECLASS-6.1	27242692
ECLASS-7.0	27242692
ECLASS-8.0	27242692
ECLASS-9.0	27242692
ECLASS-10.1	27242692
ECLASS-11.1	27242692
ECLASS-12.0	27242692
ETIM-5.0	EC001583
GTIN	4048879047890
Pakkauskoko	1
Tullinumero	85366990

Electrical data | Supply

Operating voltage DC	24 V
Operating current max.	4 A

Installation | Connection

Connection information	Han-Brid®, 6-polig
Family construction form	M12
Gender	female
Mating cycles min.	500

Installation | Pin assignment

No. of poles	6
--------------	---

Device protection | Electrical

Degree of protection (EN IEC 60529) IP65

Mechanical data | Mounting data

Height	80,5 mm
Width	40 mm
Depth	40 mm

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
Operating temperature max.	85 °C