

**MODLINK MSDD SINGLE COMBI INSERT GERMANY ORANGE**

2 x RJ45

1 x Germany (VDE) orange

2 x RJ45, 8-pole metal, CAT6A (female/female)

[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta

**Kaupalliset tiedot**

|             |               |
|-------------|---------------|
| ECLASS-6.0  | 27189234      |
| ECLASS-6.1  | 27189217      |
| ECLASS-7.0  | 27189217      |
| ECLASS-8.0  | 27189217      |
| ECLASS-9.0  | 27182806      |
| ECLASS-10.1 | 27182806      |
| ECLASS-11.1 | 27182806      |
| ECLASS-12.0 | 27182806      |
| ETIM-5.0    | EC002625      |
| GTIN        | 4048879848855 |
| Pakkauskoko | 1             |
| Tullinumero | 85366990      |

**Device protection | Electrical**

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP20 |
|-------------------------------------|------|

**Mechanical data | Mounting data**

|        |         |
|--------|---------|
| Height | 87,5 mm |
| Width  | 50,7 mm |
| Depth  | 43 mm   |

**Environmental characteristics | Climatic**

|                            |       |
|----------------------------|-------|
| Operating temperature min. | -5 °C |
| Operating temperature max. | 50 °C |

|                                       |                           |
|---------------------------------------|---------------------------|
| Storage temperature min.              | -10 °C                    |
| Storage temperature max.              | 60 °C                     |
| <b>Shielding plate</b>                |                           |
| Connection information                | Threaded hole M4          |
| Tightening torque                     | 0,9 Nm                    |
| <b>Germany (VDE)</b>                  |                           |
| Connection cross section max.         | 2,5 mm²                   |
| AWG number max.                       | 14                        |
| Operating voltage AC                  | 250 V                     |
| Operating current                     | 16 A                      |
| Connection                            | Spring clamp terminals FK |
| No. of poles                          | 2 + PE                    |
| Connections per pole                  | 2                         |
| Protection contact present            | yes                       |
| <b>RJ45</b>                           |                           |
| Operating voltage AC max. (UL-listed) | 30 V                      |
| Operating voltage DC max. (UL-listed) | 42,4 V                    |
| Current operating max. (UL)           | 175 mA                    |
| Family construction form              | RJ45                      |
| Family type Back side                 | RJ45                      |
| Cable category min.                   | Cat6a                     |
| Looking techniques                    | Snap-in connector         |