

**COMLIGHT56 LED RED STATUS LIGHT**

Input 24VDC

Compact status light  
red[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta

**Kaupalliset tiedot**

|             |               |
|-------------|---------------|
| ECLASS-6.0  | 27371220      |
| ECLASS-6.1  | 27110390      |
| ECLASS-7.0  | 27110390      |
| ECLASS-8.0  | 27110390      |
| ECLASS-9.0  | 27110350      |
| ECLASS-10.1 | 27110350      |
| ECLASS-11.1 | 27110350      |
| ECLASS-12.0 | 27110350      |
| ETIM-5.0    | EC000232      |
| GTIN        | 4048879853842 |
| Pakkauskoko | 1             |
| Tullinumero | 85319000      |

**Electrical data | Supply**

|                          |       |
|--------------------------|-------|
| Operating voltage DC     | 24 V  |
| Current consumption max. | 26 mA |

**Industrial communication | HMI**

|                    |         |
|--------------------|---------|
| Luminous intensity | 735 mcd |
|--------------------|---------|

**Device protection | Electrical**

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

**Mechanical data | Material data**

Material housing Plastic

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 61 mm |
| Width  | 56 mm |
| Depth  | 56 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 50 °C  |

**Connection type 1**

|                          |                           |
|--------------------------|---------------------------|
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| No. of poles             | 2                         |
| PIN 1                    | 24 V DC (0 V)             |
| PIN 2                    | 0 V (24 V DC)             |