

**M12 male 0° A-cod. with cable**

PUR 5x0.34 gy UL/CSA+drag ch. 1m

Male straight

A-coded




M12, 5-pole

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Further cable lengths on request.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Plastic housings with good resistance against chemicals and oils.

[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta



Cable length 1 m

**Side 1**

Tightening torque 0,6 Nm

Tämän tietolomakkeen tiedot on laadittu suurimmalla mahdollisella huolellisuudella.

Vahingonkorvausvastuu koskien tietojen oikeellisuutta, laajuutta ja ajankohtaisuutta kattaa ainoastaan törkeän laiminlyönnin. Versio: 19.05.2024

Murrelektronik Power Oy | Jussilankatu 6 | 15680 Lahti | Fon +358 20 7789810 | Fax +358 20 7789811 | shop@murrelektronik.fi | shop.murrelektronik.fi

|                                           |                                                                                                     |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Mounting method                           | inserted, screwed                                                                                   |
| Family construction form                  | M12                                                                                                 |
| Thread                                    | M12 x 1                                                                                             |
| suitable for corrugated tube (internal Ø) | 10 mm                                                                                               |
| Coding                                    | A                                                                                                   |
| Material                                  | PUR                                                                                                 |
| Width across flats                        | SW13                                                                                                |
| Degree of protection (EN IEC 60529)       | IP65, IP66K, IP67                                                                                   |
| Side 2                                    |                                                                                                     |
| Stripping length (jacket)                 | 20 mm                                                                                               |
| Kaupalliset tiedot                        |                                                                                                     |
| ECLASS-6.0                                | 27279218                                                                                            |
| ECLASS-6.1                                | 27279218                                                                                            |
| ECLASS-7.0                                | 27279218                                                                                            |
| ECLASS-8.0                                | 27279218                                                                                            |
| ECLASS-9.0                                | 27060311                                                                                            |
| ECLASS-10.1                               | 27060311                                                                                            |
| ECLASS-11.1                               | 27060311                                                                                            |
| ECLASS-12.0                               | 27060311                                                                                            |
| ETIM-5.0                                  | EC001855                                                                                            |
| GTIN                                      | 4048879572859                                                                                       |
| Pakkauskoko                               | 1                                                                                                   |
| Tullinumero                               | 85444290                                                                                            |
| Electrical data   Supply                  |                                                                                                     |
| Operating voltage AC max.                 | 125 V                                                                                               |
| Operating voltage DC max.                 | 125 V                                                                                               |
| Operating voltage AC (UL-listed)          | 30 V                                                                                                |
| Operating voltage DC (UL-listed)          | 30 V                                                                                                |
| Current operating per contact max.        | 4 A                                                                                                 |
| Installation   Connection                 |                                                                                                     |
| Stripping length (jacket)                 | 20 mm                                                                                               |
| Mounting set                              | M12 x 1                                                                                             |
| Device protection   Electrical            |                                                                                                     |
| Additional condition protection degree    | inserted, screwed                                                                                   |
| Pollution Degree                          | 3                                                                                                   |
| Rated surge voltage                       | 1,5 kV                                                                                              |
| Material group (IEC 60664-1)              | I                                                                                                   |
| Mechanical data   Material data           |                                                                                                     |
| Coating locking                           | Nickeled                                                                                            |
| Coating of fitting                        | nickel plated                                                                                       |
| Locking material                          | Zinc die-casting                                                                                    |
| Material screw connection                 | Zinc die-casting                                                                                    |
| Mechanical data   Mounting data           |                                                                                                     |
| Mounting method                           | inserted, screwed, Shaking protection                                                               |
| Environmental characteristics   Climatic  |                                                                                                     |
| Operating temperature min.                | -25 °C                                                                                              |
| Operating temperature max.                | 85 °C                                                                                               |
| Additional condition temperature range    | depending on cable quality                                                                          |
| Important installation notes              |                                                                                                     |
| Note on strain relief                     | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties. |

Note on bending radius

**Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.

| Conformity                                        |                                                                |
|---------------------------------------------------|----------------------------------------------------------------|
| Product standard                                  | DIN EN 61076-2-101 (M12)                                       |
| Installation   Cable                              |                                                                |
| Cable identification                              | 235                                                            |
| Cable Type                                        | 3                                                              |
| Jacket Color                                      | gray                                                           |
| Type of Certificate                               | cURus                                                          |
| Amount stranding                                  | 1                                                              |
| Stranding                                         | 5 wires around Core filler twisted                             |
| Filler                                            | yes                                                            |
| wire arrangement                                  | brown, black, blue, white, green-yellow                        |
| Cable weigth                                      | 41,8 g/m                                                       |
| Material jacket                                   | PUR                                                            |
| Shore hardness jacket                             | 90 ± 5 Shore A                                                 |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Outer-diameter (jacket)                           | 4,8 mm                                                         |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                          |
| Material wire insulation                          | PP                                                             |
| Amount wires                                      | 5                                                              |
| Outer diameter insulation                         | 1,25 mm                                                        |
| Outer diameter tolerance core insulation          | ± 5 %                                                          |
| Shore hardness wire insulation                    | 70 ± 5 Shore D                                                 |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Amount strands (wire)                             | 42                                                             |
| Diameter of single wires                          | 0,1 mm                                                         |
| Conductor crossection (wire)                      | 0,34 mm²                                                       |
| Material conductor wire                           | Stranded copper wire, bare                                     |
| Conductor type (wire)                             | strand class 6                                                 |
| Traversing distance (C-track)                     | 10 m @ 25 °C   horizontal                                      |
| Nominal voltage AC max.                           | 300 V                                                          |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                              |
| Current load capacity min. wire                   | 4,5 A                                                          |
| Electrical resistance line constant wire          | 57 Ω/km @ 20 °C                                                |
| AC withstand voltage (wire - wire)                | 2,5 kV @ 60 s                                                  |
| Power frequency withstand voltage (wire - jacket) | 2,5 kV @ 60 s                                                  |
| Min. operating temperature (static)               | -40 °C                                                         |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                              |
| Operating temperature min. (dynamic)              | -25 °C                                                         |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                              |
| Flame resistance                                  | IEC 60332-2-2   UL 1581 § 1090   UL 1581 § 1100 FT2            |
| chemical resistance                               | Good, application-related testing                              |
| Gasoline resistance                               | Good, application-related testing                              |
| Oil resistance                                    | Good, application-related testing   DIN EN 60811-404           |
| Bending radius (fixed)                            | 5 x Outer diameter                                             |
| Bending radius (dynamic)                          | 10 x Outer diameter                                            |
| Travel speed (C-track)                            | 10 Mio. @ 25 °C                                                |
| No. of torsion cycles                             | 2 Mio.                                                         |
| Torsion stress                                    | ± 180 °/m                                                      |
| Torsion speed                                     | 35 cycles/min                                                  |