

**M12 male 90° B-cod. with cable shielded**

PUR 1x2xAWG24 shielded vt UL/CSA+drag ch. 7.5m

PROFIBUS

Male 90°

M12, 2-pole




B-coded

shielded


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Linkki tuotteeseen](#)**Kuvat**

Tuote voi erota kuvassa olevasta



Cable length

7,5 m

**Side 1**

|                                          |                                       |
|------------------------------------------|---------------------------------------|
| Tightening torque                        | 0,6 Nm                                |
| Mounting method                          | inserted, screwed                     |
| Family construction form                 | M12                                   |
| Thread                                   | M12 x 1                               |
| Material                                 | PUR                                   |
| Width across flats                       | SW13                                  |
| Degree of protection (EN IEC 60529)      | IP65, IP66K, IP67                     |
| Kaupalliset tiedot                       |                                       |
| ECLASS-6.0                               | 27061801                              |
| ECLASS-6.1                               | 27060307                              |
| ECLASS-7.0                               | 27060307                              |
| ECLASS-8.0                               | 27060307                              |
| ECLASS-9.0                               | 27060307                              |
| ECLASS-10.1                              | 27060307                              |
| ECLASS-11.1                              | 27060307                              |
| ECLASS-12.0                              | 27060307                              |
| ETIM-5.0                                 | EC001855                              |
| GTIN                                     | 4048879344364                         |
| Pakkauskoko                              | 1                                     |
| Tullinumero                              | 85444290                              |
| Electrical data   Supply                 |                                       |
| Operating voltage AC max.                | 60 V                                  |
| Operating voltage DC max.                | 60 V                                  |
| Operating voltage AC (UL-listed)         | 30 V                                  |
| Operating voltage DC (UL-listed)         | 30 V                                  |
| Current operating per contact max.       | 4 A                                   |
| Installation   Connection                |                                       |
| Mounting set                             | M12 x 1                               |
| Device protection   Electrical           |                                       |
| Additional condition protection degree   | inserted, screwed                     |
| Mechanical data   Material data          |                                       |
| Coating locking                          | Nickeled                              |
| Coating of fitting                       | nickel plated                         |
| Locking material                         | Zinc die-casting                      |
| Material screw connection                | Zinc die-casting                      |
| Mechanical data   Mounting data          |                                       |
| Mounting method                          | inserted, screwed, Shaking protection |
| Environmental characteristics   Climatic |                                       |
| Operating temperature min.               | -25 °C                                |
| Operating temperature max.               | 85 °C                                 |
| Additional condition temperature range   | depending on cable quality            |
| Installation   Cable                     |                                       |
| Cable identification                     | 841                                   |
| Jacket Color                             | violet                                |
| Type of Certificate                      | cURus                                 |
| Amount stranding                         | 1                                     |
| Stranding                                | 2 wires with 2 Filler twisted         |
| Cable shielding (type)                   | copper braid, tinned                  |
| Cable shielding (coverage)               | 85 %                                  |
| Banding                                  | Fleece, Foil                          |
| Filler                                   | yes                                   |

|                                                         |                                                                |
|---------------------------------------------------------|----------------------------------------------------------------|
| wire arrangement                                        | red, green                                                     |
| No. of bending cycles (C-track)                         | 5 Mio. @ 25 °C                                                 |
| Cable weight                                            | 70,4 g/m                                                       |
| Material jacket                                         | PUR                                                            |
| Shore hardness jacket                                   | 87 ± 3 Shore A                                                 |
| Freedom from ingredients (jacket)                       | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Outer-diameter (jacket)                                 | 7,7 mm                                                         |
| Tolerance outer diameter (sheath)                       | ± 5 %                                                          |
| Amount wires                                            | 2                                                              |
| Outer diameter insulation                               | 2,55 mm                                                        |
| Outer diameter tolerance core insulation                | ± 5 %                                                          |
| Shore hardness wire insulation                          | 60 ± 3 Shore D                                                 |
| Ingredient freeness wire insulation                     | lead-free, cadmium-free, CFC-free, halogen-free                |
| Amount strands (wire)                                   | 19                                                             |
| Diameter of single wires                                | 24 AWG                                                         |
| Conductor crosssection (wire)                           | 24 AWG                                                         |
| Material conductor wire                                 | Stranded copper wire, bare                                     |
| Traversing distance (C-track)                           | 5 m @ 25 °C   horizontal                                       |
| Current load capacity (standard)                        | to DIN VDE 0298-4                                              |
| Current load capacity min. wire                         | 4,5 A                                                          |
| Electrical resistance line constant wire                | 72,2 Ω/km @ 20 °C                                              |
| Nominal voltage power AC max.                           | 300 V                                                          |
| Electric capacitance (power)                            | 29000 pF/km                                                    |
| AC withstand voltage power (wire - shield)              | 2 kV @ 60 s                                                    |
| Power frequency withstand voltage power (wire - jacket) | 2 kV @ 60 s                                                    |
| AC withstand voltage power (wire - wire)                | 2 kV @ 60 s                                                    |
| Min. operating temperature (static)                     | -40 °C                                                         |
| Max. operating temperature (fixed)                      | 80 °C                                                          |
| Operating temperature min. (dynamic)                    | -20 °C                                                         |
| Operating temperature max. (dynamic)                    | 70 °C                                                          |
| Flame resistance                                        | IEC 60332-2-2   UL 1581 § 1100 FT2   UL 1581 § 1090            |
| chemical resistance                                     | Good, application-related testing                              |
| Gasoline resistance                                     | Good, application-related testing                              |
| Oil resistance                                          | Good, application-related testing   DIN EN 60811-404           |
| Bending radius (fixed)                                  | 7,5 x Outer diameter                                           |
| Bending radius (dynamic)                                | 12 x Outer diameter                                            |