

M12 female recept. A-cod. shielded rear

PUR 12x0.14 shielded bk UL 2.0m

Flange female

M12, 12-pole

shielded



Rear mounting

Further cable lengths on request.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Linkki tuotteeseen

Kuvat



Tuote voi erota kuvassa olevasta



|                   |        |
|-------------------|--------|
| Cable length      | 2 m    |
| Side 1            |        |
| Tightening torque | 0,6 Nm |

|                                     |                   |
|-------------------------------------|-------------------|
| Mounting method                     | inserted, screwed |
| Family construction form            | M12               |
| Thread                              | M12 x 1           |
| Coding                              | A                 |
| Material                            | Brass             |
| No. of poles                        | 12                |
| Degree of protection (EN IEC 60529) | IP67              |

#### Kaupalliset tiedot

|             |               |
|-------------|---------------|
| ECLASS-6.0  | 27279220      |
| ECLASS-6.1  | 27279220      |
| ECLASS-7.0  | 27440103      |
| ECLASS-8.0  | 27440103      |
| ECLASS-9.0  | 27440103      |
| ECLASS-10.1 | 27440103      |
| ECLASS-11.1 | 27440103      |
| ECLASS-12.0 | 27440103      |
| ETIM-5.0    | EC002061      |
| GTIN        | 4065909070864 |
| Pakkauskoko | 1             |
| Tullinumero | 85444290      |

#### Electrical data | Supply

|                                    |       |
|------------------------------------|-------|
| Operating voltage AC max.          | 30 V  |
| Operating voltage DC max.          | 30 V  |
| Current operating per contact max. | 1,5 A |

#### Diagnostics

|                       |    |
|-----------------------|----|
| Status indication LED | no |
|-----------------------|----|

#### Installation | Connection

|                    |           |
|--------------------|-----------|
| Mounting set       | M16 x 1.5 |
| Width across flats | SW19      |

#### Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Protection NEMA                        | 3, 4, 6P          |
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 0,8 kV            |
| Material group (IEC 60664-1)           | I                 |

#### Mechanical data | Material data

|                           |               |
|---------------------------|---------------|
| Coating locking           | nickel plated |
| Coating of fitting        | nickel plated |
| Locking material          | Brass         |
| Material screw connection | Brass         |

#### Mechanical data | Mounting data

|                 |                   |
|-----------------|-------------------|
| Mounting method | inserted, screwed |
|-----------------|-------------------|

#### Environmental characteristics | Climatic

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating temperature min.             | -25 °C                     |
| Operating temperature max.             | 85 °C                      |
| Additional condition temperature range | depending on cable quality |

#### Important installation notes

|                        |                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note on strain relief  | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |

#### Approvals

|                                                   |                                                                                        |
|---------------------------------------------------|----------------------------------------------------------------------------------------|
| UL 50E                                            | yes                                                                                    |
| <b>Installation   Cable</b>                       |                                                                                        |
| Cable identification                              | 706                                                                                    |
| Cable Type                                        | 3                                                                                      |
| Jacket Color                                      | black                                                                                  |
| Type of Certificate                               | cURus                                                                                  |
| Amount stranding                                  | 1                                                                                      |
| Stranding                                         | 3 wires twisted                                                                        |
| Amount stranding (type 2)                         | 1                                                                                      |
| Stranding (type 2)                                | 9 wires around Stranding combination twisted                                           |
| Cable shielding (type)                            | copper braid, tinned                                                                   |
| Cable shielding (coverage)                        | 80 %                                                                                   |
| Banding                                           | Fleece, Foil                                                                           |
| wire arrangement                                  | gray-pink, violet, red-blue, brown, red, gray, black, yellow, pink, green, white, blue |
| Cable weighth                                     | 67,1 g/m                                                                               |
| Material jacket                                   | PUR                                                                                    |
| Shore hardness jacket                             | 90 ± 5 Shore A                                                                         |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Outer-diameter (jacket)                           | 6,5 mm                                                                                 |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                                                  |
| Material wire insulation                          | PP                                                                                     |
| Amount wires                                      | 12                                                                                     |
| Outer diameter insulation                         | 1 mm                                                                                   |
| Outer diameter tolerance core insulation          | ± 5 %                                                                                  |
| Shore hardness wire insulation                    | 70 ± 5 Shore D                                                                         |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Amount strands (wire)                             | 18                                                                                     |
| Diameter of single wires                          | 0,1 mm                                                                                 |
| Conductor crosssection (wire)                     | 0,14 mm²                                                                               |
| Material conductor wire                           | Stranded copper wire, bare                                                             |
| Conductor type (wire)                             | strand class 6                                                                         |
| Traversing distance (C-track)                     | 5 m @ 25 °C   horizontal                                                               |
| Nominal voltage AC max.                           | 300 V                                                                                  |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                                                      |
| Current load capacity min. wire                   | 2 A                                                                                    |
| Electrical resistance line constant wire          | 138 Ω/km @ 20 °C                                                                       |
| AC withstand voltage (wire - wire)                | 2 kV @ 60 s                                                                            |
| Power frequency withstand voltage (wire - jacket) | 2 kV @ 60 s                                                                            |
| AC withstand voltage (wire - shield)              | 2 kV @ 60 s                                                                            |
| Min. operating temperature (static)               | -40 °C                                                                                 |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                                                      |
| Operating temperature min. (dynamic)              | -25 °C                                                                                 |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                                                      |
| UV resistance                                     | DIN EN ISO 4892-2 A                                                                    |
| Flame resistance                                  | UL 1581 § 1100 FT2   IEC 60332-2-2   UL 1581 § 1090                                    |
| chemical resistance                               | Good, application-related testing                                                      |
| Gasoline resistance                               | Good, application-related testing                                                      |
| Oil resistance                                    | Good, application-related testing   DIN EN 60811-404                                   |
| Bending radius (fixed)                            | 5 x Outer diameter                                                                     |
| Bending radius (dynamic)                          | 10 x Outer diameter                                                                    |
| Travel speed (C-track)                            | 5 Mio. @ 25 °C                                                                         |
| No. of torsion cycles                             | 2 Mio.                                                                                 |

|                |               |
|----------------|---------------|
| Torsion stress | $\pm 30$ °/m  |
| Torsion speed  | 35 cycles/min |