




SVS VALVE PLUG FORM BI 11MM FIELD-WIREABLE

230V LED+VDR PG9

 Form BI (11 mm)
 230 V AC/DC $\pm 10\%$
 LED and VDR
 PG9

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

[Linkki tuotteeseen](#)
Kuvat


Tuote voi erota kuvassa olevasta

Side 1

Degree of protection (EN IEC 60529) IP65

Kaupalliset tiedot

ECLASS-6.0	27279221
ECLASS-7.0	27440104
ECLASS-8.0	27440104
ECLASS-9.0	27440102
ETIM-5.0	EC002062
GTIN	4048879187084

Pakkauskoko	1
Tullinumero	85366990
Electrical data	
Capacity CX	15 ms
Holding power max.	100 W
Electrical data Supply	
Operating voltage AC	230 V
Operating voltage AC min.	207 V
Operating voltage AC max.	253 V
Operating voltage DC	230 V
Operating voltage DC min.	207 V
Operating voltage DC max.	253 V
Cut-off peak voltage max.	450 V
Current consumption max.	12 mA
Diagnostics	
Status indication LED	yellow
Installation	
Connection cross section max.	1,5 mm²
Installation Connection	
Tightening torque	0,4 Nm
Mounting set	M3
Device protection Electrical	
Additional condition protection degree	inserted, locked, with screw connection
Mechanical data Mounting data	
Mounting method	PG9
Clamping range min.	6 mm
Clamping range max.	8 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C