

MQ15 female shielded field-wireable 600V AC Typ 36-pol., max. 2.5mm², 7 - 14mm

MQ15




Female straight


field-wireable

Shielded

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Linkki tuotteeseen**Kuvat**



Tuote voi erota kuvassa olevasta



Side 1	
Tightening torque	0,5 Nm
Mounting method	inserted, locked
Family construction form	MQ15
Gender	female
Coding	Type 3
Material contact	CuZn
No. of poles	6
Side 2	
Mounting method	field-wireable
Kaupalliset tiedot	
ECLASS-6.0	27279221
ECLASS-6.1	27260702
ECLASS-7.0	27440102
ECLASS-8.0	27440102
ECLASS-9.0	27440116
ECLASS-10.1	27440102
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ETIM-5.0	EC002635
GTIN	4065909100646
Pakkauskoko	1
Tullinumero	85366990
Electrical data Supply	
Operating voltage DC max.	600 V
Operating current max.	16 A
Diagnostics	
Status indication LED	no
Installation	
Connection cross section max.	2,5 mm²
Installation Connection	
Connection	Notched contact

Device protection

Shielded yes

Device protection | Electrical

Degree of protection (EN IEC 60529) IP67
Additional condition protection degree inserted, locked
Pollution Degree 3
Rated surge voltage power contacts 6 kV
Rated surge voltage signal contacts 1,5 kV
Material group (IEC 60664-1) II
Overvoltage category (EN 60950-1) III

Mechanical data | Material data

Coating contact silver-plated
Coating locking nickel plated
Material housing Zinc die-casting
Locking material Zinc die-casting

Mechanical data | Mounting data

Clamping range min. 7 mm
Clamping range max. 14 mm
Looking techniques bayonet-locking, Screw locking

Environmental characteristics | Climatic

Operating temperature min. -40 °C
Operating temperature max. 85 °C

Important installation notes

Note on strain relief Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Note on bending radius **Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.

Conformity

Product standard IEC 61076-2-116