

IO-Link-Adapter-Emparro20-Pro

IO-Link adapter for plugging onto the Emparro20-Pro switching power supplies
The IO-Link communication adapter allows diagnostics and configuration of the Emparro20-Pro switched-mode power supplies

IO-Link Device V1.1.2

[Linkki tuotteeseen](#)

Kuvat



Tuote voi erota kuvassa olevasta



General product information

Manufacturer name	Murrelektronik
Manufacturer product designation	IO-Link-Adapter-Emparro20-Pro
Manufacturer product root	Trafos/Netzgeräte
Manufacturer product family	Sonstiges
Manufacturer product type	transformers + power supply accessories
URI manufacturer	https://www.murrelektronik.com/

Electrical data | Supply

Operating voltage IO-Link DC min.	18 V
Operating voltage IO-Link DC max.	30 V

Electrical data | Input

Input voltage DC	24 V
Input voltage DC min.	18 V
Input voltage DC max.	30 V
Input current DC max.	50 mA
Input current IO-Link max.	50 mA
Voltage type input	DC

Electrical data | Output

Output current IO-Link per channel max.	50 mA
---	-------

Industrial communication | IO-Link

IO-Link revision ID	V1.1.2
---------------------	--------

IO-Link transmission rate COM2 (38.4 kbit/s)

Device ID (decimal)	524815
IO-Link process data length input	7 Bytes
IO-Link process data length output	3 Bytes
IO-Link cycle time min.	20 ms
IO-Link SIO-Mode	yes

Installation

Connection cross section min.	0,2 mm ²
Connection cross section max.	1,5 mm ²
Cross section connection with wire end ferrule min.	0,25 mm ²
Cross section connection with wire end ferrule max.	0,75 mm ²
AWG number min.	25
AWG number max.	16
Cross section connection with wire end ferrule AWG min.	24 AWG
Cross section connection with wire end ferrule AWG max.	18 AWG

Installation | Connection

Stripping length	8 mm
------------------	------

Device protection | Electrical

Installation height max. ASL	5000 m
Degree of protection (EN IEC 60529)	IP20
Pollution Degree	2
Protective circuitry input	Suppressor diode
Over voltage protection	yes

Device protection | Mechanical

Cooling type	Natural convection
--------------	--------------------

Mechanical data | Material data

Combustibility class housing (UL94)	V-0
Material housing	Plastic

Mechanical data | Mounting data

Net weight	9 g
Mounting method	geschnappt
Height	44,2 mm
Width	19,1 mm
Depth	17,5 mm

Environmental characteristics | Climatic

Ambient temperature min.	-40 °C
Ambient temperature max.	70 °C
Storage temperature min.	5 °C
Storage temperature max.	35 °C
Relative humidity min. (operation)	5 % no dew formation
Relative humidity max. (operation)	95 % no dew formation

Technical Data | Reliability

MTBF	4160000 h, DIN EN 61709:1999-01, DIN EN ISO 13849-1:2008-12, SN 29500
Additional condition MTTF, MTBF	40 °C

Environmental product conformity

REACH	(EC) No 1907/2006
REACH-SVHC	compliant

RoHS	2011/65/EU Exception 7c1
China RoHS	compliant EPUP 25
WEEE	compliant
Halogen-free-Material	Material not Halogen-free
Pb-free-Material	Material not Pb-free
Conformity	
CE	2014/30/EU
EMC	2014/30/EU
Low Voltage Directive	2014/35/EU
Approvals	
UL	E200364
Kaupalliset tiedot	
GTIN	4048879910637
Pakkauskoko	1
Tullinumero	85389099